


SEZIONE UTENSILI PER MACCHINE MANUALI

Mole a profilo a fascia continua con tastatore



Profilo A




Spessore Lastra	Legante metallico			Legante resina diamantata		
20 R10	Pos.1 FC c/tast.	Pos.2 FC c/tast.	Pos.3 FC s/tast.	Pos.4	Pos.5	Pos.6
30 R15						
40 R20						

Profilo B



Spessore Lastra	Legante metallico			Legante resina diamantata		
20	Pos.1 FC c/tast.rot.	Pos.2 FC c/tast.rot.	Pos.3 FC s/tast.	Pos.4	Pos.5	Pos.6
30						

Profilo B+B



Spessore Lastra	Legante metallico			Legante resina diamantata		
20	Pos.1 FC c/tast.rot.	Pos.2 FC c/tast.rot.	Pos.3 FC s/tast.	Pos.4	Pos.5	Pos.6
30						

Profilo E




Spessore Lastra	Legante metallico			Legante resina diamantata		
30	Pos.1 FC c/tast.rot.	Pos.2 FC c/tast.rot.	Pos.3 FC s/tast.	Pos.4	Pos.5	Pos.6

Profilo F



Spessore Lastra	Legante metallico			Legante resina diamantata		
20	Pos.1 FC c/tast.rot.	Pos.2 FC c/tast.rot.	Pos.3 FC s/tast.	Pos.4	Pos.5	Pos.6
30						

Profilo H



Spessore Lastra	Legante metallico			Legante resina diamantata		
20	Pos.1 FC c/tast.rot.	Pos.2 FC c/tast.rot.	Pos.3 FC s/tast.	Pos.4	Pos.5	Pos.6
30						

Profilo O




Spessore Lastra	Legante metallico			Legante resina diamantata		
20	Pos.1 FC c/tast.rot.	Pos.2 FC c/tast.rot.	Pos.3 FC s/tast.	Pos.4	Pos.5	Pos.6
30						

Profilo Q




Spessore Lastra	Legante metallico			Legante resina diamantata		
20	Pos.1 FC c/tast.rot.	Pos.2 FC c/tast.rot.	Pos.3 FC s/tast.	Pos.4	Pos.5	Pos.6
30						

Profilo T




Spessore Lastra	Legante metallico			Legante resina diamantata		
	20 R5	Pos.1 FC	Pos.2 FC	Pos.3 FC s/tast.	Pos.4	Pos.5
30 R5	c/tast.rot.	c/tast.rot.				

Profilo V



Spessore Lastra	Legante metallico			Legante resina diamantata		
	20	Pos.1 FC	Pos.2 FC	Pos.3 FC	Pos.4	Pos.5
30						
40	c/tast.rot.					

Profilo Z



Spessore Lastra	Legante metallico			Legante resina diamantata		
	20	Pos.1 FC	Pos.2 FC	Pos.3 FC	Pos.4	Pos.5
30	c/tast.rot.	c/tast.rot.	s/tast.			